

TITLE OF THE INVENTION

DIGITAL PRINTER AND DIGITAL CAMERA

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 11-274505, filed September 28, 1999,
the entire contents of which are incorporated herein by
reference.

BACKGROUND OF THE INVENTION

10 This invention relates to a digital printer and
a digital camera, and more particularly to a digital
printer and a digital camera, which can print image
with attendant circumstances such as a photography date
attached thereto.

15 Various types of digital video printers for
printing photographed images that are obtained by
a digital device such as a digital camera have recently
been developed. In these printers, photographed images
stored in a memory device, for example, a memory card
20 can easily be printed.

Further, there is a recent demand for developing
a digital camera provided with a printing mechanism,
or a portable printer, which enables printing of
a photographed image immediately after photographing
25 it.

A technique is well known, which is for
simultaneously recording image data and information

009260-4940960

such as a photography date, and printing the image data and the photography date superimposed thereon. For example, Japanese Patent Application KOKAI Publication No. 9-322102 discloses an apparatus in which, when printing a photograph with character data such as a date superimposed thereon, the position or the color of the date can be selected by operating a mouse.

In the above described publication, however, the orientation of character data relative to image data is fixed. In other words, the user cannot select the orientation of character data when printing image data together with the character data. In general, this does not cause any problem when printing data obtained by operating the digital camera held in a landscape position. However, in the case of data obtained by operating the camera held in a portrait position, the orientation of character data does not correspond to that of image data, which makes it difficult to read the character data.

BRIEF SUMMARY OF THE INVENTION

It is the object of the invention to provide a digital printer and a digital camera, which can provide a printing output with easy-to-read attendant information such as date information, which have a nice or good format.

To attain the object, there is provided a printer

009260-49407960

for printing an image based on image data and attendant information associated with the image data, comprising:

means for synthesizing the image data with the attendant information to produce print image data;

5 means for printing an image based on the print image data; and

means for changing an orientation of attendant information to be superimposed on the image, to one of a plurality of predetermined orientations,
10 the changing means changing the orientation of the attendant information in accordance with a predetermined operation by a user so that the attendant information is synthesized with the image, oriented appropriately for an orientation
15 of the image data.

Since the printer can change, to one of a plurality of predetermined orientations, the orientation of the attendant information to be superimposed on the image data, the orientation of the
20 attendant information can be easily made to correspond to the orientation of the image data by appropriately changing the orientation of the attendant information in accordance with the user's operation, for example, between the case of printing image data obtained by
25 operating a digital camera held in a landscape position, and the case of printing image data obtained by operating a digital camera held in a portrait

009260"440/950

position. Accordingly, the user can easily read the attendant information, and obtain a printing output that looks nice.

Moreover, According to the present invention, the orientation of the attendant information with respect to the image data is predetermined in accordance with a position on the image data, in which the attendant information is superimposed, and the changing means simultaneously changes the position and the orientation of the attendant information to be superimposed on the image data, in accordance with the user's operation of designating the position of the attendant information.

Thus relating the position of the attendant information to its orientation enables printing of the attendant information oriented appropriately for a position designated by the user. As a result, the user does not need to designate the position and the orientation of the attendant information individually. This means that the present invention has a high operability.

The processing of changing the orientation in accordance with the position can be realized by providing an operation unit including four operation sections corresponding to upward, downward, leftward and rightward, thereby setting, in accordance with a user's operation of the orientation unit, the position of the attendant information on the image data

00570464-092600

along one of upper, lower, left and right edges of the image data, and changing the orientation of the attendant information in accordance with the set position. In this case, the user can set the position and the orientation of the attendant information simply by operating one of orientation keys.

In addition, where the attendant information is situated, for example, along the lower edge of the image data, it can easily be shifted between the left end, the center, and the right end of the lower edge, using means for shifting the position of the attendant information along the one of the upper, lower, left and right edges in accordance with the user's operation of that one of the four operation sections, which corresponds to the one of the upper, lower, left and right edges. This means further enhances the operability of the present invention.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification,

illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1A is a schematic perspective view illustrating an external appearance of a digital camera according to the embodiment of the invention;

FIG. 1B is a schematic sectional view showing the internal structure of the camera;

FIG. 2 is a block diagram illustrating the system of the digital camera shown in FIGS. 1A and 1B;

FIG. 3 is a flowchart useful in explaining the flow of processing executed by the digital camera system when it is in a print mode;

FIG. 4 is a view illustrating an example of a file structure of image data recorded in a recording medium incorporated in the digital camera system shown in FIG. 2;

FIG. 5 is a view useful in explaining processing for designating character data, executed by the key operation of the digital camera shown in FIGS. 1A and 1B;

FIGS. 6A and 6B are flowcharts useful in explaining the procedure of the processing for designating character data, executed by the key operation in the digital camera system shown in

009260-13407950

FIG. 2; and

FIG. 7 is a schematic view useful in explaining the procedure of processing for moving character data, included in the character data designating processing and executed by the key operation in the digital camera system shown in FIG. 2.

DETAILED DESCRIPTION OF THE INVENTION

A digital camera according to the embodiment of the invention will be described with reference to the accompanying drawings.

Referring first to FIGS. 1A and 1B, the basic structure of the digital camera according to the embodiment will be described.

FIGS. 1A and 1B shows a digital still camera 11 provided with a photosensitive printer. In this camera, an image of an object to be photographed is formed on a solid-state photography element such as a CCD, is converted to image data indicating the photographed image, and is recorded on a recording medium such as a memory card. The image data can be read from the recording medium and a print image can printed out based on the image by the printer. When printing data, character or mark, such as a photography date, associated with image data can be superimposed on the print image.

FIG. 1A is a schematic perspective view of an external appearance of the digital camera 11

009260-1440960

when viewed from behind. As is shown in FIG. 1A,
the main body of the digital camera 11 is provided with
a release switch, i.e. a shutter button 12, a mode
switch 13, an optical viewfinder 14, an image display
5 LCD 15, a mode display LCD 16, a strobe light 17,
a cross key 18, a sheet discharge port 19, etc.

The release switch or shutter button 12 is
an operation button for inputting an instruction
to execute photography. The mode switch 13 is
10 an operation button to be used to set/change the
operation mode of the digital camera 11. The following
three operation modes are prepared for the digital
camera 11 and can be switched by the operation of
the mode switch 13.

15 1) Record/Photography mode:

In this mode, a to-be-photographed subject or
object is photographed using a solid-state photography
element such as a CCD, and image data obtained by the
photography is recorded in a recording medium.

20 2) Reproduction mode:

In this mode, data such as image data previously
obtained by photography (including image data obtained
by photography operation of another digital camera,
image data created by a computer, etc.) is read from
25 the recording medium and displayed on the image display
LCD 15.

09670464-092600

3) Print mode:

In this mode, data such as image data previously obtained by photography (including data on an image photographed by another digital camera, image data created by a computer, etc.) is read from the recording medium, and an image based on the image data is printed by the built-in printer. An image based on image data obtained by photography can be printed immediately after the photography.

In the print mode, the user can select the contents of character data to be superimposed on a to-be-printed image, and designate the position of the character data on the to-be-printed image by operating the cross key 18. More specifically, the cross key 18 is an operation button for changing the position of character data, and includes four scroll keys as shown. The position of character data is set upward when pushing the upward key, and set downward when pushing the downward key. Further, the orientation of character data is also set with the four scroll keys. The orientation of character data is set downward when pushing the upward key, and set upward when pushing the downward key.

The coordination of the position and orientation of character data enables printing of character data while orienting the character data optimally with respect to its position designated by the user.

009260-1940960

Thus, the user does not have to designate the position and the orientation individually, which means that the camera has a high operability.

FIG. 1B is a schematic sectional view of the digital camera 11 when viewed from upward.

As shown in FIG. 1B, the digital camera 11 has a photography lens section 21 on the front side of the main body, and contains, in the main body, a printed circuit board 22 provided with various electronic elements, and a printing section 23. The printing section 23 functions as a photosensitive built-in printer, and comprises a film cartridge, an optical head, etc. as shown in FIG. 1B. This photosensitive built-in printer uses a self-development type photosensitive paper (a photosensitive film) as printing paper. The photosensitive paper (film) is exposed on the basis of image data to be printed, and then executes self-development, thereby forming an image thereon.

The film cartridge (also called a "film pack") contains a plurality of photosensitive paper sheets (photosensitive films) used as printing paper sheets. This film cartridge is of a detachable type and can be detachably attached to the main body of the digital camera 11, and printing paper 200 (photosensitive paper) is supplied in units of one film cartridge.

When printing, printing paper sheets 200

009260 49407960

5
10

15

20

25

25

the shutter button 12, the mode switch 13 and the cross
key 18, the image display LCD 15, the mode display LCD
16 and the strobe light 17, the digital camera 11
comprises a photography lens system 111, a photography
5 element 112, a photography circuit 113, an A/D
converting circuit 114, a system controller 115,
a memory card interface (I/F) 116, a built-in memory
117, a display control circuit 118, an image processing
section 119, an external interface (I/F) 120,
10 an compression/decompression processing section 121,
a power supply section 122, an EEPROM 123, etc.

The photography lens system 111, the photography
element 112, the photography circuit 113 and the A/D
converter circuit 114 constitute a photography section.

15 The photography lens system 111 is an optical system
that constitutes the photography lens section 21.

The photography element 112 is a solid-type photography
element for executing photoelectric conversion to
convert a subject image, formed by the photography
20 optical system 111, into an electric image signal.
This element is formed of, for example, a CCD area
sensor provided with a color filter.

The photography circuit 113 controls the
photography element 112 so as to receive image
25 information from the element 112, to adjust the speed
of the element shutter (electronic shutter) of the
element 112, and/or to adjust the gain of an image

005260-45402960

signal output from the element 112. An image signal output from the photography circuit 113 is supplied to the A/D converter circuit 114, where it is converted into a digital image signal.

5 The system controller 115 is a CPU for controlling each unit incorporated in the digital camera 11, and is formed of, for example, a one-chip microcomputer. In this embodiment, the system controller 115 has an attendant information synthesizing/controlling
10 section 301 for controlling the process of synthesizing character data, as well as a control section for photographing, recording and printing an image. The attendant information synthesizing/controlling section 301 has an attendant information synthesizing/
15 controlling section 301 for simultaneously changing the position and the orientation of character data associated with image data. This attendant information synthesizing/controlling section 301 will be described later in detail with reference to FIGS. 5 to 7.

20 The memory card interface (I/F) 116 is provided for accessing the attachable/detachable memory 100 to read/write data. Image data is written into and read from the memory 100 via the memory card interface (I/F) 116.

25 The built-in memory 117 is a buffer area used for temporarily holding photography image data obtained by the photography section. This buffer area is

009260-1940/960

The image processing section 119 creates image data for printing by superimposing character data associated with image data on the image data. This synthesizing processing by the image processing section 119 or the compression/decompression processing by the compression/decompression processing section 121 are executed on the built-in memory 117.

The display control circuit 118 has a function of displaying image data on the image display LCD 15, and displays an original image or character data on a display section under the control of the system controller 115 when executing the character data designating processing. The external interface 120 is provided for enabling communication with an external computer or other electron devices via a communication interface such as RS232, IEEE1394, etc. The external interface 120 transmits or receives various control data items, image data, etc.

The power supply section 122 is a power supply circuit for supplying each unit of the digital camera

11 with operation power output from the batteries contained in the digital camera 11 or from an external AC power supply. The EEPROM 123 stores, for example, parameters for various image processing steps.

5 The digital camera 11 also includes, as units constituting the printing section 23, a to-be-printed image creating section 201, a printing buffer memory 202, a head driving circuit 203, an optical head section 204, a drive control circuit 205, a driving
10 section 206, a film cartridge 207, a cartridge sensor 208, etc., as is shown in FIG. 2.

 The to-be-printed image creating section 201 executes various types of image processing, such as resizing processing, gamma correction processing, color
15 correction processing, etc., on to-be-printed image data stored in the built-in memory 117 for obtaining image data suitable for printing. The section 201 rasterizes the image data for printing, and develops it in units of one line in the printing buffer memory 202.
20 The image data developed in the printing buffer memory 202 is supplied to the optical head section 204 via the head driving circuit 203. The optical head section 204 is formed of three optical heads corresponding to light beams R, G and B, and an LCD shutter for controlling,
25 in units of one pixel, interruption/transmission of light emitted from the optical heads. The control of the open period of the LCD shutter enables setting of

009260-190260

a period of exposure to each light beam R, G or B in units of one pixel. The cartridge sensor 208 detects whether or not the film cartridge 207 is mounted.

(Print mode)

5 Referring now to the flowchart of FIG. 3, a series of operations executed in the print mode will be described. In this section, a description will be given of a case where image data previously photographed and recorded in the attachable/detachable memory 100 is printed.

10 When the user has designated the print mode, the system controller 115 reads an image data file from the attachable/detachable memory 100, then controls the compression/decompression processing section 121 so as to decompress main image data contained in the image data file, and displays the decompressed data on the image display LCD 15 (step S11). The image data file includes main image data, thumbnail image data and character data such as a photography date, a file name, etc. as shown in FIG. 4.

20 When printing an image other than the displayed image (if the answer to the question of a step S12 is NO), frame feeding for reading another image from the attachable/detachable memory 100 is executed in accordance with the user's operation (step S13), thereby repeating the processing of the step S11.

After a to-be-printed image is selected (if the

009260-4940/960

answer to the question of the step S12 is YES), the system controller 115 inquires the user, by displaying, for example, a message on the image display LCD 15, whether or not character data associated with the image should be printed together with the image (step S14).

If the user designates the printing of the character data (if the answer to the question of the step S14 is YES), the system controller 115 executes character data designating processing (step S15), in which to-be-printed character data is selected, and the position and the orientation of the character data in the to-be-printed image are set. FIG. 5 shows manners of setting of the position and the orientation of character data.

As is shown in FIG. 5, character data such as a photography date is placed in a lower portion of the image and oriented upward, when the downward key included in the cross key 18 has been pushed. Accordingly, image data obtained by the digital camera 11 held in the landscape position is oriented upward as shown in FIG. 5, i.e. displayed in a correct position. Thus, when printing this image data, character data can be set in an appropriate position and oriented appropriately simply by pushing the downward key.

On the other hand, when the user has pushed the rightward key of the cross key 18, character data such as a photography date is placed on the right hand of

009260-4402950

5 Image data obtained by operating the digital
camera held in the portrait position is displayed
on the screen such that it is orientated leftward or
rightward. Therefore, when printing this image data,
character data can be set in an appropriate position
0 and oriented appropriately with respect to the
orientation of the image data, by pushing the rightward
or leftward key.

As described above, the relationship between the position and the orientation of character data is predetermined so that the character data will be always placed in a lower portion of image data irrespective of the orientation of the image data, and therefore

5

10

15

20

25

(Character Data Designating Processing)

Referring now to the flowchart of FIGS. 6A and 6B, the procedure of processing for designating character data, executed at the step S15 of FIG. 3, will be described in detail.

In the character data designating processing, the system controller 115 first determines, on the basis of the operation by the user, that any of date, time and file name should be printed, and then displays an image with date, time or file name data superimposed thereon (steps S21 - S25). The initial position of the date, time or file name data is a lower portion of the displayed image, and the orientation of the character data is set upward as usual.

After that, the system controller 115 determines whether or not the printing position of the character data should be designated, on the basis of whether or not the cross key 18 has been operated (step S26). If no orientation key of the cross key 18 is operated (if the answer to the question of the step S26 is NO), or if the downward key (lower button) of the cross key 18 is pushed, the system controller 115 situates the character data along the lower edge of the image without revolving it, i.e. keeping it oriented upward (in a default state) (step S31).

When the user has pushed the rightward key (right-hand button) (if the answer to the question of

009260"49407960

5 When the user has pushed the upward key (upper
button) (if the answer to the question of a step S29
is YES), the system controller 115 situates
the character data along the upper edge of the image,
orienting it downward by revolving the character
0 data counterclockwise or clockwise through 180 degrees
(step S33).

When the user has pushed the leftward key (left-hand button) (if the answer to the question of a step S30 is YES), the system controller 115 situates the character data along the left edge of the image, orienting it rightward by revolving the character data clockwise through 90 degrees (step S34).

Subsequently, the system controller 115 detects whether or not the user has pushed the same orientation key more than once (step S35). If the same orientation key has been pushed more than once (if the answer to the question of the step S35 is YES), the system controller 115 cyclically shifts the position of the character data, along an edge indicated by the orientation key, to "central position", "left end position", "right end position", and again "central position", "left end position" ... in this order each

time the orientation key has been pushed once
(steps S36 - S40), as is shown in FIG. 7.

FIG. 7 shows a case where the downward key has
been pushed several times. When the downward key has
5 been pushed for the first time, the character data is
initially situated in "right end position" along the
lower edge of the image. If, in this state, the
downward key is pushed again, the character data is
shifted to "central position" along the lower edge
10 of the image. If the downward key is again pushed,
the character data is further shifted to "left end
position". Similarly, if the downward key is yet again
pushed, the character data is returned to "right end
position".

15 More specifically, in the shifting processing, the
system controller 115 first determines whether or not
the present position of the character data is "right
end position" along the edge indicated by the presently
pushed orientation key (step S36). If it is determined
20 to be "right end position" (if the answer to the
question of the step S36 is YES), the position of
the character data is shifted to "central position"
(step S38).

25 On the other hand, if the present position of the
character data is not "right end position" along the
edge indicated by the presently pushed orientation key,
it is determined whether or not the present position of

09670464-092600

the character data is "left end position" (step S37).
If it is determined to be "left end position" (if the
answer to the question of the step S37 is YES), the
position of the character data is shifted to "right end
5 position" (step S39). If, on the other hand, the
present position of the character data is not "left end
position" (i.e. if the answer to the question to the
step S37 is NO and it is determined to be "central
position"), the system controller 115 shifts the
10 character data to "left end position" (step S40).

The above-described processing of controlling the
position and orientation of character data by operating
the orientation keys, and the processing of shifting
character data by continuously operating the same
15 orientation key are repeated until the user inputs
an instruction to execute printing (if the answer to
the question of a step S41 is NO).

As described above, since, in the embodiment,
the orientation of character data to be superimposed
20 on image data can be shifted to one of predetermined
upward, downward, leftward and rightward orientations
in accordance with button operations by the user.
Accordingly, character data can easily be superimposed
on to-be-printed image data, oriented appropriately
25 for the image data. In particular, relating the
position of character data to its orientation enables
superimposition and printing of character data in

009260"49407960

a position on image data, designated by the user, in a state in which the character data is oriented optimally with respect to the designated position. Thus, the digital camera has a high operability.

5 Further, the position of character data can be shifted along an edge indicated by a presently pushed orientation key, by pushing the orientation key more than once. As a result, adjustment of the position of the character data can be executed easily.

10 Although in the embodiment, character data is used as attendant information to be superimposed on to-be-printed image data, the same processing can be executed even when synthesizing image data with a figure or a mark prepared in advance and printing
15 the resultant data. Moreover, the processing may be modified such that at first, only the orientation of character data is changed by a predetermined button operation by the user, and the position of the character data is changed later, if necessary, by
20 a predetermined button operation by the user.

In addition, although the control of synthesizing attendant information according to the embodiment is suitable especially for a digital camera that has a printing function, it is also applicable, for example,
25 to a video printer having an attendant information synthesizing function, since the position and orientation of attendant information can be determined

009260-49407950

efficiently by a simple button operation. A structure obtained by removing the photography section from the digital camera of the embodiment may be used as the video printer.

5 As described above, the present invention can easily provide a printing output with easy-to-read attendant information, which looks nice.

 Additional advantages and modifications will readily occur to those skilled in the art. Therefore,
10 the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as
15 defined by the appended claims and their equivalents.

009260-1940950